

Agricultural Tires



THE SMART PARTNER FOR YOUR SUCCESS.

Mitas

Tractor radial tires



HC 2000

VF tire - Very High Flexion for high-horsepower tractors

- Lower inflation pressure provides excellent traction efficiency.
- Better ground protection due to reduced soil compaction.
- Higher load capacity for higher haulage efficiency.

Available sizes			
VF 420/85 R 28	151D	VF 480/70 R 38	172D
VF 540/65 R 30	155D	VF 520/85 R 42	174B
VF 540/65 R 30	161D	VF 650/65 R 42	170D
VF 600/70 R 30	165D	VF 710/70 R 42	179D
VF 380/85 R 34	149D	VF 480/80 R 46	164D
VF 420/85 R 34	154D	VF 480/80 R 46	175D
VF 540/65 R 34	163D	VF 480/95 R 50	170B
VF 380/95 R 38	154B	VF 380/105 R 54	168B

Tractor radial tires



SFT - Super Flexion Tire

Maximum load capacity and traction

- Developed specifically for use on high-horsepower tractors.
- Gentle ground handling for higher yields.
- Maximum traction and outstanding productivity.

Available sizes							
620/75 R 26	166A8	620/75 R 30	166D	650/85 R 38	173D	680/80 R 42	180D
750/65 R 26	166D	710/55 R 30	159D	710/70 R 38	166D	710/70 R 42	173D
750/65 R 26	171D	710/60 R 30	162D	710/70 R 38	171D	710/75 R 42	175D
540/65 R 28	142D	750/55 R 30	162D	800/70 R 38	173D	IF 900/60 R 42 CFO	192A8
600/65 R 28	154D	650/60 R 34	159D	800/70 R 38	178D	900/60 R 42	180D
600/70 R 28	157D	650/65 R 34	161D	900/60 R 38	172D	IF 710/65 R 46	183D
600/70 R 28	161D	710/60 R 34	164D	900/60 R 38	178D	710/65 R 46	174D
540/65 R 30	150D	650/65 R 38	157D	580/85 R 42	163D		
600/70 R 30	152D	650/75 R 38	169D	650/75 R 42	165D		

Tractor radial tires



AC 85

Modern all-round standard tire for all applications

- Radial tire with balanced characteristics for a wide range for applications both on the field and on the road.
- Larger ground contact area makes the tire well suited for handling grassland.
- Long service life due to wear-resistant tread compound.

Available sizes									
280/85 R 20	112A8	280/85 R 28	118A8	420/90 R 30	147A8	380/80 R 38	142A8	520/85 R 42	162A8
320/85 R 20	119A8	320/85 R 28	124A8	460/85 R 30	145A8	380/95 R 38	147D	520/85 R 42	170A8
280/85 R 24	115A8	340/85 R 28	127A8	380/85 R 34	146A8	420/85 R 38	144A8	480/80 R 46	158A8
320/85 R 24	122A8	380/85 R 28	133A8	420/85 R 34	142A8	460/85 R 38	149A8	520/85 R 46	158A8
340/85 R 24	125A8	420/85 R 28	139A8	420/85 R 34	147A8	520/85 R 38	155A8	380/90 R 50	151A8
380/85 R 24	131A8	380/85 R 30	135A8	460/85 R 34	147A8	520/85 R 38	169A8	480/80 R 50	159A8
420/85 R 24	137A8	420/85 R 30	140A8	340/85 R 38	133A8	480/80 R 42	151A8	480/95 R 50	164D

Tractor radial tires



AC 65

Powerful wide tire for all-round applications

- Gentle ground handling in the field and on grassland.
- Comfortable on the road at high speeds up to 40 mph.
- Very high transportation capability through large volume of air.
- Extremely economical due to excellent traction and low-wear tread compound.

Available sizes					
320/65 R 16	117D	600/65 R 28	147D	540/65 R 38	147D
420/65 R 20	125D	600/65 R 28 IMP	168/156A8	600/65 R 38	153D
440/65 R 24	128D	600/65 R 28 IMP	177/157A8	650/65 R 38	157D
480/65 R 24	133D	540/65 R 30	150D	650/65 R 38	166D
540/65 R 24	140D	540/65 R 30 IMP	168/156A8	650/65 R 38	173D
540/65 R 24	146D	600/65 R 30	149D	710/70 R 38	166D
440/65 R 28	131D	540/65 R 34	145D	650/65 R 42	165D
480/65 R 28	136D	600/65 R 34	151D		
540/65 R 28	142D	600/65 R 34	157D		

Tractor radial tires



HC 70

The all-round benchmark in the 70 series wide tire segment

- Higher load capacity than conventional 70 series.
- Gentle handling of the soil due to rounded shoulders and lug design.
- Wide tire shoulders provide comfortable and safe road performance.
- Low operating costs due to minimised slip.

Available sizes					
320/70 R 24	116D	420/70 R 28	133D	480/70 R 34	155D
360/70 R 24	122D	480/70 R 28	140D	520/70 R 34	148D
380/70 R 24	125D	420/70 R 30	134D	480/70 R 38	145D
420/70 R 24	130D	480/70 R 30	141D	520/70 R 38	150D
480/70 R 24	138D	480/70 R 30	152D	580/70 R 38	155D
380/70 R 28	127D	480/70 R 34	143D		

Sprayer radial tires



HC 1000

VF tire - Very High Flexion for self-propelled sprayers

- More lugs provide better durability, longer service life and lower operation cost.
- Higher maximum speed (40 mph) for less time on the road.
- Reduced soil compaction for higher loads due to lower inflation pressure.

Available sizes			
VF 650/65 R 38 NRO	180D	VF 380/105 R 50	176D
VF 380/90 R 46	173D	VF 480/80 R 50	181D
VF 750/60 R 46 NRO	189D	VF 320/105 R 54	169D

NRO (Narrow Rim NRO): The tire can also be used on a narrower rim than the standard rim.



Discover our website



Discover our mobile app



Follow us



Trelleborg Wheel Systems Americas, Inc.
570 Trelleborg Drive, Spartanburg, SC 29301
1-866-633-8473
www.mitas-tires.com/en-us

mitas-tires.com

Mitas



Pic.: AC 85 Sprayer

AC 85 Sprayer

Narrow tires developed specially for row cultivation

- Reduced tire width eases driving between plants without causing damage, contributing to higher yields.
- Deep lugs provide excellent traction, better directional stability and a high level of control.

Available sizes					
270/80 R 32	131A8 *	320/85 R 38	143A8	380/90 R 42	159A8
270/95 R 32	136A8	340/85 R 38	148A8	270/95 R 48	144A8 *
320/85 R 32	142A8	300/85 R 42	144A8 *	340/90 R 48	154A8
320/85 R 32	145A8	300/95 R 42	147A8 *	320/90 R 50	150A8
320/90 R 32	134A8	320/90 R 42	151A8	380/90 R 50	160A8
320/85 R 34	133A8	IF 320/90 R 42	155B	320/90 R 54	151A8
270/80 R 36	134A8 *	320/95 R 46	152A8	380/90 R 54	152A8
13.6 R 36	127A8 *	380/90 R 46	149A8	380/105 R 54	162D

* Tread pattern AC 90 Sprayer



Pic.: HC3000

HC 3000 & HC 3000 R

VF harvester tire - Very High Flexion for Cyclic Field Operation - CFO

- Less inflation pressure provides excellent traction efficiency.
- Higher load capacity for higher haulage efficiency.
- Larger footprint for better ground protection and reduced soil compaction.

Available sizes			
VF 750/65 R 26 CFO	180B	VF 580/85 R 42 CFO	183B
VF 1000/65 R 32 CFO	200A8 *	VF 710/70 R 42 CFO	190B
VF 580/80 R 34 CFO	178B	VF 710/70 R 42 CFO	193B
VF 520/85 R 42 CFO	177B		

* Tread pattern HC 3000 R (R = Rounded Shoulder)



SFT CHO - Cyclic Harvesting Operation

More load at lower tire pressure

- Maximum load capacity for Cyclic Harvesting Operation.
- Minimum inflation pressure during cyclic harvest operation.
- Good driving stability in road application.
- Reduces soil compaction due to a large footprint.
- Fulfills all legal requirements (limited vehicle width).

Available sizes					
680/85 R 32 CHO	178A8*	1050/50 R 32 CHO	184A8	900/60 R 38 CHO	181D
800/70 R 32 CHO	175A8	1250/50 R 32 CHO	194A8	680/80 R 42 CHO	180D
900/60 R 32 CHO	176A8	680/80 R 38 CHO	179D	800/70 R 42 CHO	182D
900/70 R 32 CHO	182A8	800/70 R 38 CHO	178D	900/60 R 42 CHO	183D
900/70 R 32 CHO	188A8	800/70 R 38 CHO	181D		

* Tread pattern AC 70 G



Pic.: SFT

SFT, AC 70H/G/N & AC 75G

Economical tire for gentle ground handling on harvesters

- Harvester tire with high load capacity and low inflation pressure.
- Wide and even distribution of ground pressure minimises pressure on the soil resistance.
- Low vibration on the road.
- High mileage performance.

Available sizes SFT				AC 70H/G/N & AC 75G	
1000/50 R 25	178A8	1250/50 R 32	188A8	650/75 R 32	167A8 ²
620/75 R 26	166B	1250/50 R 32	194A8	650/75 R 32	167A8 ¹
620/75 R 30	166D	900/60 R 38	178D	IF 650/75 R 32 CFO	176 A8 ¹
800/70 R 32	175A8	580/85 R 42	163D	650/75 R 32	172A8 ³
900/60 R 32	176A8	580/85 R 42	168D	680/85 R 32	178A8 ³
900/60 R 32	181A8	680/80 R 42	180D	800/65 R 32	172A8 ²
900/70 R 32	188A8	IF 900/60 R 42 CFO	192A8	800/65 R 32	178A8 ⁴
1050/50 R 32	178A8				

¹ AC 75G; ² AC 70H; ³ AC 70G; ⁴ AC 70N



Pic.: AGRITERRA 02

AGRITERRA 02, 03 & 04

Fast and powerful trailer tires for wide range of applications

- High load capacity due to high volume of tire.
- Steel belt under the tread for high speed capability and long lifetime.
- Excellent cost efficiency due to low rolling resistance.

Available sizes AGRITERRA 02			AGRITERRA 03 & 04		
500/60 R 22.5 IMP	161D	710/45 R 22.5 IMP	165D	600/60 R 30.5 IMP	173D ⁴
560/45 R 22.5 IMP	152D	600/55 R 26.5 IMP	165D	680/60 R 30.5 IMP	176D ³
560/45 R 22.5 IMP	160D	650/55 R 26.5 IMP	169D	750/60 R 30.5 IMP	181D ³
VF 560/60 R 22.5 IMP	166D	650/65 R 26.5 IMP	174D	800/65 R 32 IMP	185D ⁴
560/60 R 22.5 IMP	165D	710/50 R 26.5 IMP	170D		
600/50 R 22.5 IMP	163D	800/45 R 26.5 IMP	174D		
600/50 R 22.5 IMP	167D	710/50 R 30.5 IMP	173D		
620/40 R 22.5 IMP	158D	850/50 R 30.5 IMP	182D		

³ AGRITERRA 03; ⁴ AGRITERRA 04



HCM - High Capacity Municipal

All-purpose quiet-running tire for all terrains and applications

- Particularly suitable for municipal and road maintenance tractors and equipment. Designed for all-season use.
- High durability due to steel belted radial construction and unique design within its central area.
- Exceptional traction characteristics due to more edges on the lugs. The tire has a specifically developed soft compound to work on low temperatures and icy surfaces.

Available sizes					
340/80 R 18 IND	138D	360/80 R 28 IND	141D	440/80 R 34 IND	155D
360/80 R 20 IND	143D	440/80 R 28 IND	151D	480/80 R 34 IND	159D
360/80 R 24 IND	139D	440/80 R 30 IND	153D	480/80 R 38 IND	161D
400/80 R 24 IND	144D	400/80 R 28 IND	146D	540/80 R 38 IND	167D
440/80 R 24 IND	149D	540/65 R 30 IND	156D	650/65 R 42 IND	171D



TD-02

Universal tread pattern with excellent traction for a wide range of applications.



TD-13

A classic design for tractors, well-tested and proven.

Available Sizes TD-02			
8.3 - 24	8 PR	11.2 - 28	8 PR
9.5 - 24	6 PR	12.4 - 28	8 PR
11.2 - 24	8 PR	16.9 - 34	10 PR
12.4 - 24	8 PR	18.4 - 34	12 PR
16.9 - 24	8 PR *		

* Irrigation

Available Sizes TD-13			
6.00 - 16	6 PR	18.4 - 30	12, 14 PR
7.50 - 16	6 PR	18.4 - 30	14 PR
7.50 - 20	6 PR	12.4 - 36	12 PR
8.3 - 20	6 PR	13.6 - 36	6 PR
16.9 - 24	8 PR	11.2 - 38	4 PR
16.9 - 28	8, 12 PR	13.6 - 38	6, 14 PR
16.9 - 30	10, 12 PR	16.9 - 38	8 PR



TD-19

Traction tread pattern with larger rib surface in the central part.



TD-17

Pattern featuring increased tread lug depth giving better traction and less slip in difficult conditions.

Available Sizes TD-19			
11.2 - 24	8,10 PR	13.6 - 28	6 PR
12.4 - 24	8, 12 PR	14.9 - 28	8 PR
13.6 - 24	8 PR	18.4 - 34	8, 12 PR
14.9 - 24	8 PR	16.9 - 38	8 PR
18.4 - 26	12 PR	18.4 - 38	8 PR
12.4 - 28	6,10 PR		

Available Sizes TD-17	
16.9 - 30	10 PR
16.9 - 34	8 PR
12.4 - 38	8 PR